

USAGE AREAS:

It is suitable for use in outdoor and indoor sports facilities, concerts and event areas.

SYSTEM DEFINITION:

Produced in accordance with standards, the Competition Substitute Bench seat is a fixed system with a durable internal skeleton.



FEATURES:

Competition Substitute Bench seat offers comfortable and practical use with its ergonomic design, easy assembly and durability.

COMPETITION SUBSTITUTE BENCH SEAT

TECHNICAL SPECIFICATIONS

SEAT AND BACK UNITS

- 1 It is designed in accordance with human anatomy and is produced from polyurethane material in aluminum molds with a density of 50+-10% and in accordance with Mvss 302 fire standards.
- 2 There is a durable internal skeleton made of metal profile inside the seat and back pads.
- 3 The seating parts of the seats are manufactured as fixed.

CARRIER LEGS AND ARMRESTS

- 1 The foot connection parts of the seats are made of pipe with a diameter of 100 mm and a wall thickness of 2.5 mm, and the connection parts to the floor are made of sheet metal with a thickness of at least 2 mm, and are formed by molding to add durability.
- 2 The armrests are mounted on a metal frame and have plastic cups that are resistant to impacts. The armrests are upholstered in faux leather.
- 3 The armrests between rows of seats are used in common.
- 4 The seats are fixed to the floor with a single leg using suitable fasteners.
- 5 The seats are fixed to the floor with a single leg using suitable fasteners.

FABRIC / FAUX LEATHER

- 1 The material chosen for artificial leather upholstery contains 80% polyurethane and 20% polyester and is resistant to friction, flame retardant and colorfast.
- 2 Friction resistance is minimum 40,000 cycles and weight is 550 gr/m2.
- 3 The seat and back pads of the seats are covered with artificial leather with the specified properties, and impact-resistant plastic covers are mounted underneath them.






PRODUCT IMAGES



COLOURS



TECHNICAL DRAWING



PHOTOS FROM PRODUCTION



CHAMPION SUBSTITUTE BENCH SEAT

APPLICATION AREAS

